

## Connecting Link Pewag CWP connex

---

### Product information



Universal connecting link consisting of two die-forged identical halves, a bolt and a safety sleeve.

... [Read more](#)

---

**Material:** Alloy steel

**Marking:** According to standard, CE-marked, Pewag or PW, winner pro or 12, H16, batch code and type.

**Temperature range:** -60°C up to +300°C.

**Finish:** Light blue powdercoated.

**Standard:** EN 1677-1

**Warning:** Not to be heat-treated.

**Safety factor:** 4:1

**Grade:** 12

## Connecting Link Pewag CWP connex

### Blueprint



### Technical data

| Part code  | Code   | Chain diameter mm | WLL ton | b mm mm | c mm | d mm mm | e mm mm | g mm mm | s mm mm | t mm | Weight kg |
|------------|--------|-------------------|---------|---------|------|---------|---------|---------|---------|------|-----------|
| 11.0789314 | CWP 7  | 7                 | 2.36    | 51      | 11.5 | 9       | 63      | 17      | 13      | 15.5 | 0.24      |
| 11.0787965 | CWP 8  | 8                 | 3       | 58      | 14   | 10      | 62      | 20      | 15      | 20   | 0.27      |
| 11.0789315 | CWP 10 | 10                | 5       | 66      | 18   | 13      | 78      | 22      | 21      | 25   | 0.57      |
| 11.0789316 | CWP 13 | 13                | 8       | 84      | 22   | 17      | 107     | 25      | 25      | 34   | 1.43      |
| 11.0750093 | CWP 16 | 16                | 12.5    | 120     | 27   | 21      | 128     | 48      | 31      | 41   | 2.26      |