Lifting Solutions Group
Axel Johnson International

BLCW special grab

Product information



General:

For vertical lifting and moving of various materials as steel, wood, plastic, concrete, marble etc. which have parallel sides. The clamp is locked in the open position. To perform lifting, the operator must activate the handle and hold it up while the force on the lifting eye is going upwards. When laying down the load, the clamp automatically unlocks itself to open.

The pads are covered with special plastic to avoid damage of contact surfaces

... Read more

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

BLCW special grab

Blueprint



Technical data

Part code	Code	WLL ton	Beam width mm	S mm	T mm	U mm	V mm	X mm	Y mm	Weight kg
502300051100030	BLCW 0.5 t	0.5	30-110	95	45	305-460	270-325	80 (*70)	15	7
502300102300030	BLCW 1 t	1	100-230	120	45	380-655	425-530	80 (*70)	15	12.3
502300203600030	BLCW 2 t	2	220-360	140	45	410-735	580-675	80 (*70)	15	18
502300305000030	BLCW 3 t	3	350-500	178	64	530-900	725-835	100 (*90)	16	33

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved