

## Round Sling - Blackline

---

### Product information



### **POWERTEX**

Typically used in connection with theaters, scenes etc. where the round sling preferably should not be visible.

Design: Load carrying yarn covered with "seamless" black protection sleeve.

Stretch with working load: 2-3%.

Length tolerance: Nominal length (EWL)  $\pm 2\%$ .

... [Read more](#)

---

**Material:** Polyester. Resistant to most acids but not to strong alkalizes.

**Marking:** According to standard, CE-marked, Manufacture ID, WLL, length, date.


**Temperature range:** Approx.  $-40^{\circ}$  up to  $+100^{\circ}\text{C}$ .

**Standard:** EN 1492-2

**Safety factor:** 7:1

## Round Sling - Blackline

### Blueprint



### Technical data

| Part code        | Code      | WLL<br>ton | EWL<br>m | WLL Straight Lift<br>ton | Choke Hitch<br>ton | Basket Hitch 0°<br>ton | Basket Hitch 0-45°<br>ton | Basket Hitch 45°-60°<br>ton | WLL 0-45°<br>t | Colour |
|------------------|-----------|------------|----------|--------------------------|--------------------|------------------------|---------------------------|-----------------------------|----------------|--------|
| 12.2014922011010 | PRS-011.B | 1.1        | 1        | 1.1                      | 0.9                | 2.2                    | 1.5                       | 1.1                         | 1.5            | Black  |
| 12.2014922021010 | PRS-021.B | 2.1        | 1        | 2.1                      | 1.7                | 4.2                    | 2.9                       | 2.1                         | 2.9            | Black  |
| 12.2014922031010 | PRS-031.B | 3.1        | 1        | 3.1                      | 2.5                | 6.2                    | 4.3                       | 3.1                         | 4.3            | Black  |