

Round Sling - Blackline

Product information



POWERTEX

Typically used in connection with theaters, scenes etc. where the round sling preferably should not be visible.

Design: Load carrying yarn covered with "seamless" black protection sleeve.

Stretch with working load: 2-3%.

Length tolerance: Nominal length (EWL) $\pm 2\%$.

... [Read more](#)

Material: Polyester. Resistant to most acids but not to strong alkalizes.

Marking: According to standard, CE-marked, Manufacture ID, WLL, length, date.

Temperature range: Approx. -40° up to $+100^{\circ}\text{C}$.

Standard: EN 1492-2

Safety factor: 7:1

Round Sling - Blackline

Blueprint



Technical data

Part code	Code	WLL ton	EWL m	WLL Straight Lift ton	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	WLL 0-45° t	Colour
12.2014922011010	PRS-011.B	1.1	1	1.1	0.9	2.2	1.5	1.1	1.5	Black
12.2014922021010	PRS-021.B	2.1	1	2.1	1.7	4.2	2.9	2.1	2.9	Black
12.2014922031010	PRS-031.B	3.1	1	3.1	2.5	6.2	4.3	3.1	4.3	Black