

## Fast Connector Socket FCS



### Product information

Forged clevis fittings with Pin and cutterpin for fast connection of steel wire rope. Can be used to terminate all constructions of wire rope including high performance ropes, anti-rotation ropes and standard 6 strand ropes.  
The connector has to be moulded / casted on the steel wire rope with wirelock resin.

**Features:** Designed for use with mobile cranes.

**Material:** Quenched and tempered cast steel.

**Finish:** Blue painted (P) or hot dip galvanized (G).

**Warning:** Compare the spelter's and the wire rope's minimum breaking load.

Part Code	Code	Rope Ø range mm	MBL	Finish	TB mm	TL mm	A mm	B mm	C mm	Ø H mm	Ø P mm	T mm	W mm	D mm	Ø D mm	Ø J mm	K mm	Weight kg
01-7015013P	FCS 701 P	11-13	20	Painted	67	150	62	61	27	15	25	12	25	50	33	49	46	1.6
01-7015016P	FCS 702 P	13-16	25	Painted	85	182	72	78	32	18	30	14	32	58	38	60	59	2.6
01-7015019P	FCS 703 P	16-19	40	Painted	95	218	85	93	40	21	35	16	38	70	45	70	69	4.5
01-7015023P	FCS 704 P	20-22	55	Painted	110	253	102	106	45	24	41	19	44	80	50	82	81	6.5
01-7015026P	FCS 705 P	23-26	75	Painted	128	298	115	123	60	28	51	22	51	104	60	95	90	11
01-7015029P	FCS 706 P	27-29	90	Painted	142	357	140	152	65	32	57	25	57	114	70	107	116	16

## Blueprint

