



## Super Reeve Connector Socket SCS - with bolt

### Product information

A revolutionary evolution of the Fast Connector Socket. This socket line has the smallest connector diameter available in the market today, and still meets the respective EN standards. It has been designed to go through the smallest spaces in a crane reeving system.

This unique patent pending design allows refitting by pouring in the field, saving valuable down time compared to swaging techniques.

The standard finish of our sockets is blue. Hot dipped galvanized is also available.

**Material:** Quenched and tempered cast steel.

Part code	Code	Rope Ø range mm	MBL ton	Finish	A mm	B mm	C mm	Ø H mm mm	Ø P mm mm	T mm	W mm mm	D, mm	Ø D mm mm	Ø J mm mm	L mm	TL mm mm	TB mm mm	Weight kg
10.10SCS902B	SCS 902 B	13-16	25	Painted	85	133	32	19	30	14	32	58	32	56	98	250	96	3.1
10.10SCS903B	SCS 903 B	16-19	40	Painted	90	160	40	22	35	16	38	70	40	65	114	290	107	4.8
10.10SCS904B	SCS 904 B	20-22	55	Painted	107	184	45	26	41	19	44	80	44	77	130	336	123	8
10.10SCS904B.GAL	SCS 904 B.GAL	20-22	55	Galvanized	107	184	45	26	41	19	44	80	44	77	130	336	123	8
10.10SCS905B	SCS 905 B	23-26	75	Painted	115	211	60	31	50	22	51	104	52	88	142	386	141	12
10.10SCS906B	SCS 906 B	27-29	90	Painted	140	215	65	34	57	25	57	114	58	96	159	420	160	16
10.10SCS907B	SCS 907 B	30-32	125	Painted	150	260	73	36	63	28	63	126	64	110	177	483	165	23
10.10SCS908B	SCS 908 B	33-36	125	Painted	170	260	73	40	64	28	69	126	68	114	197	503	185	25
10.10SCS908B.GAL	SCS 908 B.GAL	33-36	125	Galvanized	170	260	73	40	64	28	69	126	68	114	197	503	185	25

## Blueprint

