



Short Bow Socket SBS

Product information

The "ultimate" socket for dynamic loads. Towing lines, anchor lines and chain-rope connections used by major offshore contractors. Quenched and tempered cast steel with extremely high mechanical values for unmatched weight to MBL ratio. All spelter sockets have a 100% efficiency on wire rope MBL.

The standard finish of our sockets is blue but hot dipped galvanized is also available.

Standard: EN 10204-2.1 declaration of conformity / EN 10204-3.1 material certificate.

Material: Quenched and tempered cast steel.

Marking: According to standard

Standard: EN 10204

Part code	Rope Ø range mm	MBL ton	Finish	Model	Rope Ø inch	A mm	B mm	C mm	øH	K mm	TA mm	TL mm	Weight kg
10.42445120010	31-36	140	Painted	SBS 512	1 1/4 - 1 3/8	141	83	38	39	75	132	262	7
-	31-36	140	Galvanized	SBS 512	1 1/4 - 1 3/8	141	83	38	39	75	132	262	7
10.42445170010	37-42	160	Painted	SBS 517	1 1/2 - 1 5/8	162	103	40	44	92	152	305	10
-	37-42	160	Galvanized	SBS 517	1 1/2 - 1 5/8	162	103	40	44	92	152	305	10
10.424.5190010	43-48	200	Painted	SBS 519	1 3/4 - 1 7/8	188	120	48	51	112	178	356	16
-	43-48	200	Galvanized	SBS 519	1 3/4 - 1 7/8	188	120	48	51	112	178	356	16
10.42445220010	49-54	250	Painted	SBS 522	2 - 2 1/8	204	132	54	59	120	200	390	21
-	49-54	250	Galvanized	SBS 522	2 - 2 1/8	204	132	54	59	120	200	390	21

10.42445240010	55-60	320	Painted	SBS 524	21/4 - 23/8	230	148	62	64	135	220	440	28
-	55-60	320	Galvanized	SBS 524	21/4 - 23/8	230	148	62	64	135	220	440	28
10.42445260010	61-68	400	Painted	SBS 526	21/2 - 25/8	265	165	68	73	150	250	198	44
-	61-68	400	Galvanized	SBS 526	21/2 - 25/8	265	165	68	73	150	250	198	44
10.42445270010	69-75	500	Painted	SBS 527	23/4 - 27/8	287	178	75	79	164	274	540	53
-	69-75	500	Galvanized	SBS 527	23/4 - 27/8	287	178	75	79	164	274	540	53
10.42445280010	76-80	600	Painted	SBS 528	3 - 35/8	314	195	76	89	175	295	585	70
-	76-80	600	Galvanized	SBS 528	3 - 35/8	314	195	76	89	175	295	585	70
10.42445290010	81-86	700	Painted	SBS 529	31/4 - 33/8	327	216	82	92	194	320	625	81
-	81-86	700	Galvanized	SBS 529	31/4 - 33/8	327	216	82	92	194	320	625	81
10.42445300010	87-93	800	Painted	SBS 530	31/2 - 35/8	358	220	92	99	202	350	670	112
-	87-93	800	Galvanized	SBS 530	31/2 - 35/8	358	220	92	99	202	350	670	112
10.42445310010	94-102	900	Painted	SBS 531	33/4 - 4	365	235	100	108	215	375	700	130
-	94-102	900	Galvanized	SBS 531	33/4 - 4	365	235	100	108	215	375	700	130
10.42445330010	108-115	1,000	Painted	SBS 533	41/4 - 41/2	420	270	110	120	240	410	800	182
-	108-115	1,000	Galvanized	SBS 533	41/4 - 41/2	420	270	110	120	240	410	800	182

Blueprint

