



## Single Sheave Crane Blocks

### Product information

**General:**

- Standard fitted with becket, cylindrical roller bearing and reeving guide.
- Standard fitted with Crosby type of swivel only hook (319AN style), including safety latch and split pin.
- Standard painted yellow (no striping).
- This crane block may be used with 2 lines only as well.
- Sheaves may be adjusted for other wire rope diameters.
- Becket suitable for connecting Open Wedge Socket for indicated wire rope.
- Becket can not be adjusted.

| Part code        | WLL ton | Rope Ø mm | Sheave dia. mm | øD1 | øD2 | B mm | O mm | S mm | TA mm | TB mm | TL mm | T mm | øZ | Weight kg |
|------------------|---------|-----------|----------------|-----|-----|------|------|------|-------|-------|-------|------|----|-----------|
| 16.1321250051111 | 5       | 11        | 250/210        | 250 | 210 | 348  | 34   | 30   | 320   | 103   | 523   | 20   | 27 | 41        |
| 16.1321260051113 | 5       | 13        | 260/221        | 260 | 221 | 353  | 34   | 30   | 353   | 109   | 525   | 22   | 27 | 67        |
| 16.1321260081114 | 8       | 14        | 260/218        | 260 | 218 | 390  | 43   | 35   | 330   | 121   | 571   | 28   | 32 | 80        |
| 16.1321300081113 | 8       | 13        | 300/255        | 300 | 255 | 426  | 43   | 30   | 370   | 101   | 621   | 22   | 27 | 89        |
| 16.1321300081116 | 8       | 16        | 300/252        | 300 | 252 | 420  | 43   | 35   | 370   | 111   | 621   | 28   | 32 | 94        |
| 16.1321300101116 | 10      | 16        | 300/252        | 300 | 252 | 459  | 52   | 35   | 370   | 127   | 659   | 28   | 32 | 91        |
| 16.1321260101114 | 10      | 14        | 260/218        | 260 | 218 | 429  | 52   | 35   | 330   | 137   | 609   | 28   | 32 | 93        |
| 16.1321350101116 | 10      | 16        | 350/305        | 350 | 305 | 499  | 52   | 35   | 435   | 107   | 739   | 28   | 33 | 113       |
| 16.1321400121118 | 12      | 18        | 400/345        | 400 | 345 | 557  | 57   | 45   | 500   | 125   | 832   | 35   | 37 | 162       |
| 16.1321450161120 | 16      | 20        | 450/390        | 450 | 390 | 592  | 57   | 50   | 550   | 131   | 917   | 35   | 43 | 206       |
| 16.1321500201122 | 20      | 22        | 500/430        | 500 | 430 | 592  | 76   | 50   | 600   | 148   | 1,032 | 40   | 43 | 284       |

# Blueprint

