

Standard Reeve Crane Blocks 1 Sheave

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

... [Read more](#)

Standard Reeve Crane Blocks 1 Sheave

Blueprint



Standard Reeve Crane Blocks 1 Sheave

Technical data

WLL ton	Model	Rope Ø mm	Sheave dia. mm	Hook size	øD1 mm	øD2 mm	B mm	O mm	TA mm	TB mm	TLmm mm	L mm	T mm	øZ mm	Weight kg
12.5	SRB 225 .14 .1 .12.5 .E	14	260 / 255	5	260	225	523	55	35	170	789	913	28	32	75
12.5	SRB 260 .14 .1 .12.5 .E	14	300 / 260	5	300	260	548	55	400	185	933	648	28	32	110
12.5	SRB 260 .16 .1 .12.5 .E	16	300 / 260	5	300	260	548	55	400	185	933	948	28	32	110
16	SRB 225 .14 .1 .16 .E	14	260 / 255	5	260	225	548	55	345	180	923	938	28	32	100
16	SRB 260 .16 .1 .16 .E	16	300 / 260	5	300	260	548	55	400	195	933	948	28	32	110
16	SRB 285 .16 .1 .16 .E	16	320 / 280	6	320	280	608	57	420	165	908	1,033	28	32	160
16	SRB 320 .16 .1 .16 .E	16	365 / 320	6	365	320	628	59	450	205	951	1,076	28	32	160
16	SRB 320 .19 .1 .16 .E	19	365 / 320	6	365	320	628	59	450	205	951	1,081	35	37	160
16	SRB 355 .16 .1 .16 .E .A	16	410 / 355	6	410	355	668	59	500	195	1,013	1,138	28	32	180
16	SRB 355 .19 .1 .16 .E	19	410 / 355	6	410	355	668	59	500	195	1,013	1,138	28	32	180
20	SRB 355 .19 .1 .20 .E	19	410 / 355	8	410	355	713	76	500	225	1,053	1,204	35	37	225
29	SRB 400 .22 .1 .29 .E	22	460 / 400	8	460	400	743	69	570	240	1,128	1,273	40	43	290
32	SRB 450 .24 .1 .32 .E .A	24	515 / 450	10	515	450	833	76	600	350	1,256	1,422	45	52	455
32	SRB 450 .26 .1 .32 .E .A	26	515 / 450	10	515	450	833	76	600	350	1,256	1,422	45	52	455
32	SRB 450 .24 .1 .32 .E .B	24	515 / 450	10	515	450	833	76	600	410	1,256	1,422	45	52	590
32	SRB 450 .26 .1 .32 .E .B	26	515 / 450	10	515	450	833	76	600	410	1,256	1,422	45	52	590
40	SRB 450 .24 .1 .40 .E .B	24	515 / 450	12	515	450	1,074	84	600	410	1,487	1,665	45	52	590
40	SRB 450 .26 .1 .40 .E	26	515 / 450	12	515	450	918	84	605	323	1,338	1,516	45	52	590
50	SRB 528 .24 .1 .50 .E	24	596 / 528	16	596	528	934	97	710	353	1,412	1,604	45	52	725
50	SRB 528 .26 .1 .50 .E	26	596 / 528	16	596	528	934	97	710	353	1,412	1,604	45	52	725
50	SRB 528 .28 .1 .50 .E	28	595 / 528	16	595	528	934	97	740	353	1,412	1,614	50	59	725
50	SRB 575 .28 .1 .50 .E	28	650 / 575	16	650	575	958	97	770	333	1,459	1,661	50	59	930
63	SRB 630 .32 .1 .63 .E	32	720 / 630	16	720	630	985	97	825	353	1,521	1,728	60	66	1,000
63	SRB 670 .28 .1 .63 .E	28	760 / 670	16	760	670	1,173	97	870	473	1,738	1,940	50	59	1,800
63	SRB 670 .32 .1 .63 .E	32	760 / 670	16	760	670	1,173	97	870	473	1,738	1,940	60	66	1,800