



Standard Reeve Crane Blocks 1 Sheave

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

| WLL ton | Model | Rope Ø mm | Sheave dia. mm | Hook size | øD1 | øD2 | B mm | O mm | TA mm | TB mm | TL mm | L | T mm | øZ | Weight kg |
|---------|-------------------------|-----------|----------------|-----------|-----|-----|------|------|-------|-------|-------|-------|------|----|-----------|
| 12.5 | SRB 225 .14 .1 .12,5 .E | 14 | 260 / 255 | 5 | 260 | 225 | 523 | 55 | 35 | 170 | 789 | 913 | 28 | 32 | 75 |
| 12.5 | SRB 260 .14 .1 .12,5 .E | 14 | 300 / 260 | 5 | 300 | 260 | 548 | 55 | 400 | 185 | 933 | 648 | 28 | 32 | 110 |
| 12.5 | SRB 260 .16 .1 .12,5 .E | 16 | 300 / 260 | 5 | 300 | 260 | 548 | 55 | 400 | 185 | 933 | 948 | 28 | 32 | 110 |
| 16 | SRB 225 .14 .1 .16 .E | 14 | 260 / 255 | 5 | 260 | 225 | 548 | 55 | 345 | 180 | 923 | 938 | 28 | 32 | 100 |
| 16 | SRB 260 .16 .1 .16 .E | 16 | 300 / 260 | 5 | 300 | 260 | 548 | 55 | 400 | 195 | 933 | 948 | 28 | 32 | 110 |
| 16 | SRB 285 .16 .1 .16 .E | 16 | 320 / 280 | 6 | 320 | 280 | 608 | 57 | 420 | 165 | 908 | 1,033 | 28 | 32 | 160 |

| | | | | | | | | | | | | | | | |
|----|--------------------------|----|-----------|----|-----|-----|-------|----|-----|-----|-------|-------|----|----|-------|
| 16 | SRB 320 .16 .1 .16 .E | 16 | 365 / 320 | 6 | 365 | 320 | 628 | 59 | 450 | 205 | 951 | 1,076 | 28 | 32 | 160 |
| 16 | SRB 320 .19 .1 .16 .E | 19 | 365 / 320 | 6 | 365 | 320 | 628 | 59 | 450 | 205 | 951 | 1,081 | 35 | 37 | 160 |
| 16 | SRB 355 .16 .1 .16 .E .A | 16 | 410 / 355 | 6 | 410 | 355 | 668 | 59 | 500 | 195 | 1,013 | 1,138 | 28 | 32 | 180 |
| 16 | SRB 355 .19 .1 .16 .E | 19 | 410 / 355 | 6 | 410 | 355 | 668 | 59 | 500 | 195 | 1,013 | 1,138 | 28 | 32 | 180 |
| 20 | SRB 355 .19 .1 .20 .E | 19 | 410 / 355 | 8 | 410 | 355 | 713 | 76 | 500 | 225 | 1,053 | 1,204 | 35 | 37 | 225 |
| 29 | SRB 400 .22 .1 .29 .E | 22 | 460 / 400 | 8 | 460 | 400 | 743 | 69 | 570 | 240 | 1,128 | 1,273 | 40 | 43 | 290 |
| 32 | SRB 450 .24 .1 .32 .E .A | 24 | 515 / 450 | 10 | 515 | 450 | 833 | 76 | 600 | 350 | 1,256 | 1,422 | 45 | 52 | 455 |
| 32 | SRB 450 .26 .1 .32 .E .A | 26 | 515 / 450 | 10 | 515 | 450 | 833 | 76 | 600 | 350 | 1,256 | 1,422 | 45 | 52 | 455 |
| 32 | SRB 450 .24 .1 .32 .E .B | 24 | 515 / 450 | 10 | 515 | 450 | 833 | 76 | 600 | 410 | 1,256 | 1,422 | 45 | 52 | 590 |
| 32 | SRB 450 .26 .1 .32 .E .B | 26 | 515 / 450 | 10 | 515 | 450 | 833 | 76 | 600 | 410 | 1,256 | 1,422 | 45 | 52 | 590 |
| 40 | SRB 450 .24 .1 .40 .E .B | 24 | 515 / 450 | 12 | 515 | 450 | 1,074 | 84 | 600 | 410 | 1,487 | 1,665 | 45 | 52 | 590 |
| 40 | SRB 450 .26 .1 .40 .E | 26 | 515 / 450 | 12 | 515 | 450 | 918 | 84 | 605 | 323 | 1,338 | 1,516 | 45 | 52 | 590 |
| 50 | SRB 528 .24 .1 .50 .E | 24 | 596 / 528 | 16 | 596 | 528 | 934 | 97 | 710 | 353 | 1,412 | 1,604 | 45 | 52 | 725 |
| 50 | SRB 528 .26 .1 .50 .E | 26 | 596 / 528 | 16 | 596 | 528 | 934 | 97 | 710 | 353 | 1,412 | 1,604 | 45 | 52 | 725 |
| 50 | SRB 528 .28 .1 .50 .E | 28 | 595 / 528 | 16 | 595 | 528 | 934 | 97 | 740 | 353 | 1,412 | 1,614 | 50 | 59 | 725 |
| 50 | SRB 575 .28 .1 .50 .E | 28 | 650 / 575 | 16 | 650 | 575 | 958 | 97 | 770 | 333 | 1,459 | 1,661 | 50 | 59 | 930 |
| 63 | SRB 630 .32 .1 .63 .E | 32 | 720 / 630 | 16 | 720 | 630 | 985 | 97 | 825 | 353 | 1,521 | 1,728 | 60 | 66 | 1,000 |
| 63 | SRB 670 .28 .1 .63 .E | 28 | 760 / 670 | 16 | 760 | 670 | 1,173 | 97 | 870 | 473 | 1,738 | 1,940 | 50 | 59 | 1,800 |
| 63 | SRB 670 .32 .1 .63 .E | 32 | 760 / 670 | 16 | 760 | 670 | 1,173 | 97 | 870 | 473 | 1,738 | 1,940 | 60 | 66 | 1,800 |

