

Standard Reeve Crane Blocks 2 Sheaves

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

... [Read more](#)

Standard Reeve Crane Blocks 2 Sheaves

Blueprint



Technical data

| WLL ton | Model | Rope Ø mm | Hooksize | Weight kg |
|---------|--------------------------|-----------|----------|-----------|
| 16 | SRB 285 .16 .2 .16 .E | 16 | 6 | 95 |
| 16 | SRB 260 .14 .2 .16 .E | 14 | 6 | 130 |
| 16 | SRB 260 .16 .2 .16 .E | 16 | 6 | 130 |
| 20 | SRB 285 .16 .2 .20 .E .A | 16 | 8 | 130 |
| 20 | SRB 285 .16 .2 .20 .E .B | 16 | 8 | 150 |
| 20 | SRB 320 .16 .2 .20 .E | 16 | 8 | 160 |
| 25 | SRB 320 .16 .2 .25 .E | 16 | 8 | 205 |
| 29 | SRB 355 .19 .2 .29 .E | 19 | 8 | 250 |
| 29 | SRB 400 .22 .2 .29 .E | 22 | 8 | 320 |
| 40 | SRB 450 .24 .2 .40 .E | 24 | 12 | 550 |
| 50 | SRB 450 .26 .2 .50 .E | 26 | 16 | 550 |
| 63 | SRB 528 .26 .2 .63 .E | 26 | 16 | 980 |
| 80 | SRB 528 .28 .2 .80 .E | 28 | 20 | 1,000 |
| 100 | SRB 670 .28 .2 .100 .E | 28 | 20 | 2,240 |
| 100 | SRB 670 .32 .2 .100 .E | 32 | 20 | 2,240 |