MENNENS | Lifting Solutions Group
Axel Johnson International

# Standard Reeve Crane Blocks 3 Sheaves

**Product information**



**General:**
- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

**Options:**
- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

**Important:**
**Inquiries for custom versions are welcome!**

... *Read more*


**Mennens Nederland**
website@mennens.nl
+31 (0)10 4373033

© October 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

# Standard Reeve Crane Blocks 3 Sheaves

## Blueprint



## Technical data

| Part code | WLL ton | Model | Rope Ø mm | Hook size | Weight kg |
|---|---|---|---|---|---|
| 6097SRB26014325E | 25 | SRB 260 .14 .3 .25 .E | 14 | 8 | 210 |
| 6097SRB26016325E | 25 | SRB 260 .16 .3 .25 .E | 16 | 8 | 210 |
| 6097SRB28516329E | 29 | SRB 285 .16 .3 .29 .E | 16 | 8 | 210 |
| 6097SRB32016329E | 29 | SRB 320 .16 .3 .29 .E | 16 | 8 | 225 |
| 6097SRB35519332E | 32 | SRB 355 .19 .3 .32 .E | 19 | 10 | 325 |
| 6097SRB36019340E | 40 | SRB 360 .19 .3 .40 .E | 19 | 12 | 455 |
| 6097SRB40022340E | 40 | SRB 400 .22 .3 .40 .E | 22 | 12 | 500 |
| 6097SRB40022350E | 50 | SRB 400 .22 .3 .50 .E | 22 | 16 | 500 |
| 6097SRB40022350E | 50 | SRB 400 .22 .3 .50 .E | 22 | 16 | 540 |
| 6097SRB45022363E | 63 | SRB 450 .22 .3 .63 .E | 22 | 16 | 680 |
| 6097SRB45024363E | 63 | SRB 450 .24 .3 .63 .E | 24 | 16 | 770 |
| 6097SRB45026363E | 63 | SRB 450 .26 .3 .63 .E | 26 | 16 | 770 |
| 6097SRB52826380E | 80 | SRB 528 .26 .3 .80 .E | 24 | 20 | 1,270 |
| 6097SRB52826380E | 80 | SRB 528 .26 .3 .80 .E | 26 | 20 | 1,270 |
| 6097SRB528263100E | 100 | SRB 528 .26 .3 .100 .E | 26 | 25 | 1,270 |
| 6097SRB528283100E | 100 | SRB 528 .28 .3 .100 .E | 28 | 25 | 1,270 |
| 6097SRB670283125E | 125 | SRB 670 .28 .3 .125 .E | 28 | 25 | 2,900 |
| 6097SRB670323125E | 125 | SRB 670 .32 .3 .125 .E | 32 | 25 | 2,900 |

**Mennens Nederland**
website@mennens.nl
+31 (0)10 4373033

© October 2026 - All Rights Reserved