

Fast Reeve Crane Blocks 4 sheave

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

[... Read more](#)

Fast Reeve Crane Blocks 4 sheave

Blueprint



Fast Reeve Crane Blocks 4 sheave

Technical data

WLL ton	Model	Rope Ø mm	Sheave dia. mm	Hooksize	Ø D1 mm	Ø D2 mm	B mm	Omm mm	TA mm	TBmm mm	TLmm mm	L mm	T mm	Ø Z mm	Weight kg
35	FRB 285 .16 .4 .35 .E	16	320 / 285	12	320	285	753	84	420	292	1,053	1,171	28	32	275
50	FRB 355 .19 .4 .50 .E	19	410 / 355	12	410	355	959	84	500	363	1,229	1,347	35	37	500
63	FRB 400 .22 .4 .63 .E	22	460 / 400	16	460	400	1,038	97	570	350	1,333	1,465	40	43	540
63	FRB 355 .19 .4 .63 .E	19	410 / 355	16	410	355	1,038	97	500	343	1,308	1,440	35	37	570
63	FRB 450 .22 .4 .63 .E	22	510 / 450	16	515	450	1,038	97	600	400	1,448	1,580	40	43	750
63	FRB 450 .24 .4 .63 .E	24	510 / 450	16	515	450	1,038	97	600	400	1,448	1,580	45	52	750
80	FRB 450 .24 .4 .80 .E	24	510 / 450	20	515	450	1,183	110	600	527	1,568	1,718	45	52	1,000
80	FRB 450 .26 .4 .80 .E	26	510 / 450	20	515	450	1,183	110	600	527	1,568	1,718	40	52	1,000
80	FRB 528 .24 .4 .80 .E	24	590 / 528	20	595	528	1,272	110	710	527	1,736	1,886	45	52	1,000
80	FRB 528 .26 .4 .80 .E	26	590 / 528	20	595	528	1,272	110	710	527	1,736	1,886	45	52	1,000
80	FRB 528 .28 .4 .80 .E	28	590 / 528	20	595	528	1,273	110	710	472	1,671	1,821	40	59	1,270
100	FRB 528 .26 .4 .100 .E	26	590 / 528	25	595	528	1,288	132	710	472	1,743	1,913	40	52	1,270
100	FRB 528 .28 .4 .100 .E	28	590 / 528	25	595	528	1,288	132	710	472	1,753	1,923	40	59	1,270
125	FRB 575 .28 .4 .125 .E	28	650 / 575	32	650	575	1,413	137	770	442	1,893	2,083	40	59	1,360
160	FRB 670 .28 .4 .160 .E	28	760 / 670	40	760	670	1,616	167	870	662	2,181	2,393	50	59	3,150
160	FRB 670 .32 .4 .160 .E	32	760 / 670	40	760	670	1,616	167	870	662	2,181	2,393	60	66	3,150