

Fast Reeve Crane Blocks 5 sheave

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

[... Read more](#)

Fast Reeve Crane Blocks 5 sheave

Blueprint



Technical data

| WLL ton | Model | Rope Ø mm | Sheave dia. mm | Hooksize | B mm | L mm | O mm | T mm | TA mm | TB mm | TLmm mm | Ø D1 mm mm | Ø D2 mm mm | Ø Z mm mm | Weight kg |
|---------|---------------------------|-----------|----------------|----------|-------|-------|------|------|-------|-------|---------|------------|------------|-----------|-----------|
| 50 | FRB 355 .16 .5 .50 .E | 16 | 410 / 355 | 12 | 959 | 1,342 | 84 | 28 | 500 | 382 | 1,224 | 410 | 355 | 32 | 500 |
| 63 | FRB 360 .19 .5 .63 .E | 19 | 420 / 360 | 16 | 973 | 1,375 | 97 | 30 | 510 | 422 | 1,243 | 420 | 360 | 37 | 600 |
| 63 | FRB 400 .19 .5 .63 .E | 19 | 460 / 400 | 16 | 1,048 | 1,520 | 97 | 30 | 570 | 432 | 1,388 | 460 | 400 | 37 | 750 |
| 80 | FRB 450 .22 .5 .80 .E | 22 | 515 / 450 | 20 | 1,188 | 1,730 | 110 | 30 | 600 | 437 | 1,580 | 515 | 450 | 43 | 815 |
| 80 | FRB 450 .24 .5 .80 .E | 24 | 515 / 450 | 20 | 1,188 | 1,730 | 110 | 40 | 600 | 437 | 1,580 | 515 | 450 | 52 | 815 |
| 80 | FRB 360 .19 .5 .80 .E | 19 | 420 / 360 | 20 | 1,082 | 1,502 | 110 | 30 | 510 | 482 | 1,352 | 420 | 360 | 37 | 820 |
| 80 | FRB 400 .19 .5 .80 .E | 19 | 460 / 400 | 20 | 1,147 | 1,597 | 110 | 30 | 570 | 507 | 1,447 | 460 | 400 | 37 | 820 |
| 100 | FRB 450 .24 .5 .100 .E | 24 | 515 / 450 | 25 | 1,263 | 1,768 | 132 | 45 | 600 | 417 | 1,598 | 515 | 450 | 52 | 910 |
| 100 | FRB 450 .26 .5 .100 .E .A | 26 | 515 / 450 | 25 | 1,263 | 1,768 | 132 | 40 | 600 | 417 | 1,598 | 515 | 450 | 52 | 910 |
| 100 | FRB 450 .26 .5 .100 .E .B | 26 | 515 / 450 | 25 | 1,263 | 1,768 | 132 | 40 | 600 | 507 | 1,598 | 515 | 450 | 52 | 1,140 |
| 125 | FRB 528 .24 .5 .125 .E | 24 | 595 / 528 | 32 | 1,333 | 1,913 | 137 | 45 | 710 | 622 | 1,723 | 595 | 528 | 52 | 1,820 |
| 125 | FRB 528 .26 .5 .125 .E | 26 | 595 / 528 | 32 | 1,333 | 1,913 | 137 | 45 | 710 | 622 | 1,723 | 595 | 528 | 52 | 1,820 |
| 125 | FRB 528 .28 .5 .125 .E | 28 | 595 / 528 | 32 | 1,333 | 1,913 | 137 | 50 | 710 | 622 | 1,723 | 595 | 528 | 59 | 1,820 |
| 150 | FRB 528 .26 .5 .150 .E | 26 | 595 / 528 | 40 | 1,333 | 1,935 | 167 | 50 | 710 | 602 | 1,723 | 595 | 528 | 52 | 1,820 |
| 150 | FRB 528 .28 .5 .150 .E | 28 | 595 / 528 | 40 | 1,333 | 1,938 | 167 | 50 | 710 | 622 | 1,726 | 595 | 528 | 59 | 1,820 |
| 150 | FRB 575 .28 .5 .150 .E | 28 | 650 / 575 | 40 | 1,383 | 2,015 | 167 | 50 | 770 | 572 | 1,803 | 650 | 575 | 52 | 1,820 |
| 160 | FRB 528 .28 .5 .160 .E | 28 | 595 / 528 | 40 | 1,502 | 2,191 | 167 | 50 | 710 | 662 | 1,979 | 595 | 528 | 59 | 2,270 |
| 160 | FRB 575 .28 .5 .160 .E | 28 | 650 / 575 | 40 | 1,591 | 2,223 | 167 | 50 | 770 | 592 | 2,011 | 650 | 575 | 59 | 2,270 |
| 200 | FRB 670 .28 .5 .200 .E | 28 | 760 / 670 | 50 | 1,716 | 2,442 | 188 | 50 | 870 | 782 | 2,206 | 760 | 670 | 59 | 3,560 |
| 200 | FRB 670 .32 .5 .200 .E | 32 | 760 / 670 | 50 | 1,716 | 2,442 | 188 | 60 | 870 | 782 | 2,206 | 760 | 670 | 66 | 3,560 |