

Fast Reeve Crane Blocks 5 sheave

Product information



General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent block change is required.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- 4 or 8 point hook locking device.
- Fast reeve guide for fast reeving.
- Safety latch with locking pin.
- C3M finish in signal yellow with black striping.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.


Important:

Inquiries for custom versions are welcome!

[... Read more](#)

Fast Reeve Crane Blocks 5 sheave

Blueprint



Technical data

WLL ton	Model	Rope Ø mm	Sheave dia. mm	Hooksize	B mm	L mm	Omm mm	T mm	TA mm	TBmm mm	TLmm mm	Ø D1 mm	Ø D2 mm	Ø Z mm	Weight kg
50	FRB 355 .16 .5 .50 .E	16	410 / 355	12	959	1,342	84	28	500	382	1,224	410	355	32	500
63	FRB 360 .19 .5 .63 .E	19	420 / 360	16	973	1,375	97	30	510	422	1,243	420	360	37	600
63	FRB 400 .19 .5 .63 .E	19	460 / 400	16	1,048	1,520	97	30	570	432	1,388	460	400	37	750
80	FRB 450 .22 .5 .80 .E	22	515 / 450	20	1,188	1,730	110	30	600	437	1,580	515	450	43	815
80	FRB 450 .24 .5 .80 .E	24	515 / 450	20	1,188	1,730	110	40	600	437	1,580	515	450	52	815
80	FRB 360 .19 .5 .80 .E	19	420 / 360	20	1,082	1,502	110	30	510	482	1,352	420	360	37	820
80	FRB 400 .19 .5 .80 .E	19	460 / 400	20	1,147	1,597	110	30	570	507	1,447	460	400	37	820
100	FRB 450 .24 .5 .100 .E	24	515 / 450	25	1,263	1,768	132	45	600	417	1,598	515	450	52	910
100	FRB 450 .26 .5 .100 .E .A	26	515 / 450	25	1,263	1,768	132	40	600	417	1,598	515	450	52	910
100	FRB 450 .26 .5 .100 .E .B	26	515 / 450	25	1,263	1,768	132	40	600	507	1,598	515	450	52	1,140
125	FRB 528 .24 .5 .125 .E	24	595 / 528	32	1,333	1,913	137	45	710	622	1,723	595	528	52	1,820
125	FRB 528 .26 .5 .125 .E	26	595 / 528	32	1,333	1,913	137	45	710	622	1,723	595	528	52	1,820
125	FRB 528 .28 .5 .125 .E	28	595 / 528	32	1,333	1,913	137	50	710	622	1,723	595	528	59	1,820
150	FRB 528 .26 .5 .150 .E	26	595 / 528	40	1,333	1,935	167	50	710	602	1,723	595	528	52	1,820
150	FRB 528 .28 .5 .150 .E	28	595 / 528	40	1,333	1,938	167	50	710	622	1,726	595	528	59	1,820
150	FRB 575 .28 .5 .150 .E	28	650 / 575	40	1,383	2,015	167	50	770	572	1,803	650	575	52	1,820
160	FRB 528 .28 .5 .160 .E	28	595 / 528	40	1,502	2,191	167	50	710	662	1,979	595	528	59	2,270
160	FRB 575 .28 .5 .160 .E	28	650 / 575	40	1,591	2,223	167	50	770	592	2,011	650	575	59	2,270
200	FRB 670 .28 .5 .200 .E	28	760 / 670	50	1,716	2,442	188	50	870	782	2,206	760	670	59	3,560
200	FRB 670 .32 .5 .200 .E	32	760 / 670	50	1,716	2,442	188	60	870	782	2,206	760	670	66	3,560