

Samson wire rope blocks 3 sheave



Product information

General:

- Up to 30 ton blocks standard supplied with swivel oval eye.
- Over 30 ton blocks standard supplied with swivel stud eye.
- Blocks can be supplied with swivel hook, swivel stud eye or swivel jaw on request.
- Standard supplied with bronze bearings. Other bearings available on request.
- Groove in sheave may be adjusted to other wire rope diameters on request.
- Blocks can be supplied with becket on request.

Temperature range: -40°C / +80°C

Note: WLL= Working Load Limit on head fitting

Safety factor: 4:1

Part code	WLL ton	Rope Ø mm	No of Sheaves	Weight kg
16.13111250230	2	10	3	9
16.13111500430	4	12	3	17
16.13112000630	6	14	3	28
16.13112500830	8	18	3	46
16.13113001030	10	20	3	69
16.13113501230	12	22	3	99
16.13113501630	16	24	3	120
16.13114001630	16	24	3	157
16.13113502030	20	24	3	143
16.13114002030	20	24	3	184
16.13113502530	25	24	3	170
16.13114002530	25	24	3	198
16.13114502530	25	28	3	220
16.13114003030	30	28	3	215
16.13114503030	30	28	3	255
16.13114004030	40	28	3	250
16.13114504030	40	28	3	295
16.13114505030	50	28	3	335

Blueprint

