

Overhaul Ball with Swivel Eye-Hook



Product information

The weight of the overhaul balls in this segment are based on average boom lengths and efficiency loss in mobile and crawler cranes. The low friction and easy to access hook swivel design makes the OHB series an excellent choice for a wide variety of crane applications.

- Bottom and top swiveling hook
- High quality, low friction thrust bearing
- Becket size optimized for Ropeblock Sockets such as Open Wedge (OWS), Open Spelter Sockets (OSS), Fast Connector Sockets (FCS) or Super Reeve Connector Sockets (SCS)
- Forged high tensile steel DIN hooks
- Body made of forged bar material
- High impact resistant body

Temperature range: -40 up to +80°C

Finish: C3M finish, signal yellow

Safety factor: 4:1

Part code	WLL ton	Rope Ø mm	B mm	O mm	TA mm	TL mm	T mm	øZ mm	Weight kg
10.9956002000334	3.2	11-13	200	41	220	500	22	27	60
10.9956004000534	3.2	14-16	200	41	220	505	28	32	60
10.9956004000834	5	14-16	220	49	238	566	28	32	80
10.9956004501034	6.3	14-16	220	49	238	566	28	32	80
10.9956004501334	8	18-19	310	49	257	719	35	37	130
10.9956005001634	8	18-19	340	49	278	681	35	37	170
10.9956006000334	8	18-19	400	49	318	864	35	37	250

Blueprint

