Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock Falz IV Standing Seam

Productinformatie



Stainless steel anchor point ABS-Lock Falz IV Standing Seam clamped onto two metal seams - completely penetration-free.
Seam intervals: 300 - 450 mm/420 - 660 mm. This stainless steel anchorage point can be installed on standing seam roofs made of steel, copper, aluminium or titanium zinc without penetrating the roof surface.

Force directions: Lateral
Substructure: Seam roofs, profile roof
Attachment: Clamped, w/o roof penetration
Application: Profile roof, flat roofs

... *Read more*

Markering: Volgens norm, CE
Norm: EN 795, CEN/TS/16415

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved

MENNENS | Lifting Solutions Group
Axel Johnson International

Anchor Point ABS-Lock Falz IV Standing Seam

Technische gegevens

Artikelnr.	Code	Max. aantal personen
8415PF4CU450	PF-4-CU-450	3
8415PF4CU660	PF-4-CU-660	3
8415PF4ST450	PF-4-ST-450	3
8415PF4ST660	PF-4-ST-660	3

Mennens Nederland
website@mennens.nl
+31 (0)10 4373033

© November 2026 - All Rights Reserved