

## Anchor Point ABS-Lock III-ST

### Productinformatie



Stainless steel anchor point ABS-Lock III-ST (Ø 16 mm) is a fall protection solution for steel (roofs, walls, facades and overhead installation) designed for countering or cementing-in. Inserted into a predrilled hole and countered using a nut. Incl. installation set. Protruding and non-protruding models available.

Add a supporting tube for usage as a corner or curve element in a lifeline system.

**Force directions:** Lateral and axial

**Substructure:** Steel

**Attachment:** Countered, screwed

**Application:** Flat roofs, facade/wall, overhead

**Markering:** Volgens norm, CE

**Norm:** EN 795, CEN/TS/16415

| Artikelnr.         | Max. aantal<br>personen | Lengte<br>mm | Draadlengte<br>mm |
|--------------------|-------------------------|--------------|-------------------|
| 19.10L3-ST-000-045 | 3                       | -            | 45                |
| 19.10L3-ST-000-100 | 3                       | -            | 100               |
| 19.10L3-ST-050-045 | 3                       | 50           | 45                |
| 19.10L3-ST-100-045 | 3                       | 100          | 45                |
| 19.10L3-ST-200-045 | 3                       | 200          | 45                |
| 19.10L3-ST-300-045 | 3                       | 300          | 45                |
| 19.10L3-ST-400-045 | 3                       | 400          | 45                |
| 19.10L3-ST-500-045 | 3                       | 500          | 45                |
| 19.10L3-ST-600-045 | 3                       | 600          | 45                |