



6x19S+staalkern

Productinformatie



Typical applications: Skidding winches.

Standard: EN 12385-4.

Design: Ordinary right hand lay.

Fill factor: 0,57

ISO 4309 Rope Category No: All Diameters RCN.02

Stalkabelconstructie: 6x19S+stk

Markering: Volgens norm

Norm: EN 12385-4

Vulfactor: 0.57

RCN: 02

| Artikelnr. | Kabel Ø mm | Treksterkte N/mm ² | Afwerking | Slagwijze | MBF (kN) | Materiaaldoorsnede mm ² | Lubrication | Gewicht kg/100m |
|-----------------|---------------|----------------------------------|-----------|-----------|----------|---------------------------------------|------------------|--------------------|
| 01.G10163050G-S | 5 | 1.960 | Verzinkt | sZ | 17,4 | 11,2 | SupplierStandard | 10 |
| 01.G10163060G-S | 6 | 1.960 | Verzinkt | sZ | 25,1 | 16,2 | SupplierStandard | 14,4 |
| 01.G10163080G-S | 8 | 1.960 | Verzinkt | sZ | 44,7 | 28,7 | SupplierStandard | 25,6 |
| 01.G10163100G-S | 10 | 1.960 | Verzinkt | sZ | 69,8 | 44,9 | SupplierStandard | 40 |
| 01.G10163120G-S | 12 | 1.960 | Verzinkt | sZ | 100 | 64,7 | SupplierStandard | 57,6 |
| 01.G10163140G-S | 14 | 1.960 | Verzinkt | sZ | 137 | 88 | SupplierStandard | 78,4 |